

# K-WV 5/3 ELEKTROPNEU MITTELSTELLUNG

5/3-way pilot valves (monostable)

**HANSA FLEX**

## Lastnosti

|                        |   |
|------------------------|---|
| Obratovalni tlak       | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\n vacuum up to 10 bar (external pilot air) |
| min. delovni tlak      | 2.5 bar (monostable), 1.0 bar (bistable)  |
| območje temperatur:    | -10 °C to +60 °C  |
| pretok 6 bar in 10 bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)             |
| pretok 6 bar in 5 bar  | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)              |



## Navodilo

Drugi podatki na zahtevo.

## Artikel

| Opis           | Priključek | Napetost     | DN | funkcija | številka vezalne sheme |
|----------------|------------|--------------|----|----------|------------------------|
| K- 07 15 03 30 | G 1/8      | 24 V DC      | 5  | 5/3-way  | 37                     |
| K- 07 15 03 31 | G 1/4      | 24 V DC      | 8  | 5/3-way  | 37                     |
| K- 07 15 25 87 | G 3/8      | 24 V DC      | 13 | 5/3-way  | 37                     |
| K- 07 15 03 32 | G 1/2"     | 24 V DC      | 15 | 5/3-way  | 37                     |
| K- 07 15 03 33 | G 1/8      | 230 V, 50 Hz | 5  | 5/3-way  | 37                     |
| K- 07 15 03 34 | G 1/4      | 230 V, 50 Hz | 8  | 5/3-way  | 37                     |
| K- 07 15 25 88 | G 3/8      | 230 V, 50 Hz | 13 | 5/3-way  | 37                     |
| K- 07 15 03 35 | G 1/2"     | 230 V, 50 Hz | 15 | 5/3-way  | 37                     |
| K- 07 15 03 36 | G 1/8      | 24 V DC      | 5  | 5/3-way  | 38                     |
| K- 07 15 03 37 | G 1/4      | 24 V DC      | 8  | 5/3-way  | 38                     |
| K- 07 15 25 89 | G 3/8      | 24 V DC      | 13 | 5/3-way  | 38                     |
| K- 07 15 03 38 | G 1/2"     | 24 V DC      | 15 | 5/3-way  | 38                     |
| K- 07 15 03 39 | G 1/8      | 230 V, 50 Hz | 5  | 5/3-way  | 38                     |
| K- 07 15 03 40 | G 1/4      | 230 V, 50 Hz | 8  | 5/3-way  | 38                     |
| K- 07 15 25 90 | G 3/8      | 230 V, 50 Hz | 13 | 5/3-way  | 38                     |
| K- 07 15 03 41 | G 1/2"     | 230 V, 50 Hz | 15 | 5/3-way  | 38                     |
| K- 07 15 03 42 | G 1/8      | 24 V DC      | 5  | 5/3-way  | 39                     |
| K- 07 15 25 91 | G 3/8      | 24 V DC      | 13 | 5/3-way  | 39                     |
| K- 07 15 03 43 | G 1/4      | 24 V DC      | 8  | 5/3-way  | 39                     |
| K- 07 15 03 44 | G 1/2"     | 24 V DC      | 15 | 5/3-way  | 39                     |
| K- 07 15 03 45 | G 1/8      | 230 V, 50 Hz | 5  | 5/3-way  | 39                     |
| K- 07 15 03 46 | G 1/4      | 230 V, 50 Hz | 8  | 5/3-way  | 39                     |
| K- 07 15 25 92 | G 3/8      | 230 V, 50 Hz | 13 | 5/3-way  | 39                     |
| K- 07 15 03 47 | G 1/2"     | 230 V, 50 Hz | 15 | 5/3-way  | 39                     |