

# K-WV 3/2 MANU PILZTAST

3/2-way pilot valve, manually operated, with mushroom pushbutton, NC

**HANSA FLEX**

## Lastnosti

|                               |   |
|-------------------------------|---|
| <b>Obratovalni tlak</b>       | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| <b>območje temperatur:</b>    | -10 °C to +60 °C  |
| <b>pretok 6 bar in 10 bar</b> | 550 NI/min  |
| <b>pretok 6 bar in 5 bar</b>  | 400 NI/min  |
| <b>sprožitev</b>              | Monostable  |
| <b>ohišje ventila</b>         | aluminij  |
| <b>vzmet</b>                  | Special steel   |
| <b>bat</b>                    | Aluminium   |
| <b>tesnilni material</b>      | NBR   |



## Navodilo

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.

Drugi podatki na zahtevo.

## Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

## Artikel

| Opis           | Priključek | simbol | sprožitev  |
|----------------|------------|--------|------------|
| K- 07 15 00 86 | G 1/8      | 13     | monostable |