

K-WV 5/2 MANU K DREHHEBEL

5/2-way pilot valves, manually operated, with short wing lever

HANSA FLEX

Lastnosti

| | |
|-------------------------------|---|
| Obratovalni tlak | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| območje temperatur: | -10 °C to +60 °C |
| pretok 6 bar in 10 bar | 550 NI/min |
| pretok 6 bar in 5 bar | 400 NI/min |
| ohišje ventila | aluminij |
| vzmet | Special steel |
| bat | Aluminium |
| tesnilni material | NBR |



Navodilo

*3 valve positions only in conjunction with a second way valve.

Drugi podatki na zahtevo.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Artikel

| Opis | Priključek | simbol | sprožitev | položaji stikala |
|----------------|------------|--------|------------|------------------|
| K- 07 15 02 37 | G 1/8 | 5 | monostable | 2 |
| K- 07 15 02 38 | G 1/8 | 6 | bistabilno | 2 |
| K- 07 15 02 39 | G 1/8 | 7 | monostable | 3* |
| K- 07 15 02 40 | G 1/8 | 8 | bistabilno | 3* |