


K-WV 5/2 PNEUMATISCH

5/2-way pilot valves

HANSA FLEX

Lastnosti

Obratovalni tlak	Max. vacuum 10 bar
min. delovni tlak	2.5 bar (monostable), 1.0 bar (bistable)
območje temperatur:	-10 °C to +60 °C
pretok 6 bar in 10 bar	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
pretok 6 bar in 5 bar	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)
priključek za krmilni zrak	G 1/8



Navodilo

Drugi podatki na zahtevo.

Artikel

Opis	Priključek	DN	funkcija	številka vezalne sheme	Krmiljenje
K- 07 15 02 11	G 1/8	5	5/2-way	27	
K- 07 15 02 12	G 1/4	8	5/2-way	27	
K- 07 15 25 70	G 3/8	13	5/2-way	27	
K- 07 15 02 15	G 1/2"	15	5/2-way	27	
K- 07 15 02 13	G 1/8	5	5/2-way	28	
K- 07 15 02 14	G 1/4	8	5/2-way	28	
K- 07 15 25 71	G 3/8	13	5/2-way	28	
K- 07 15 02 16	G 1/2"	15	5/2-way	28	