

K-VORFILTER METALLBEHAEL MULTIFIX

Pre-filters with metal bowl

HANSA FLEX

Lastnosti

vstopni tlak	Max. 16 bar
temperatura medija	max. 60 °C
temperatura okolice	Max. 60 °C
finoča filtra	0,30 µm
izkoristek	99.999 %
tesnilni material	NBR
filtrski vložek	Paper-POM
ohišje	Die-cast zinc
Drain valve	Semi-automatic
meritev pretoka	FV at P1 = 6 bar and $\Delta p = 0.02$ bar



Navodilo

* = Dimensions with adapter plate!

Drugi podatki na zahtevo.

Opis

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Dodatne informacije

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

Artikel

Opis	Navoj	pretok (L/min)	A (mm)	B	C (mm)	D (mm)	DN
K- 07 25 10 69	G 1/4	160	47,8	152,5 mm	27,0	125,5	6
K- 07 25 10 72	G 1/2	500	68,8	182,7 mm (187,7 mm)*	72,0	149,2	15

Nadomestni deli

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler