


# K-FI AK KOH METALLBEHAEL MULTIFIX

Activated carbon filters with metal bowl

**HANSA FLEX**

## Lastnosti

vstopni tlak	Max. 16 bar
temperatura medija	max. 60 °C
temperatura okolice	Max. 60 °C
tesnilni material	NBR
filtrski vložek	Activated carbon-POM
ohišje	Die-cast zinc
Drain valve	Semi-automatic
preostanek olja	0.005 mg/m <sup>3</sup>
meritev pretoka	FA at P1 = 6 bar and $\Delta p = 0.2$ bar



## Navodilo

Drugi podatki na zahtevo.

## Opis

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Artikel

Opis	Navoj	pretok (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Velikost
K- 07 25 10 49	G 1/4	380	47,8	137,0 mm	27,0	110,0	6	1
K- 07 25 10 52	G 1/2	1500	68,8	168,2 mm	34,5	133,7	15	2

## Nadomestni deli

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler