# K-RUNDDUESE LAERMARME

Low-noise round nozzles



## Navodilo

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

## Opis

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

## Artikel

| Opis | Navoj | dolžina (mm) | Ø šob zunaj (mm) | Material: | diagram C |
|---|---|---|---|---|---|
| **K- 07 10 09 56** | G 3/8 male | 55,0 | 11 | Nickel-plated brass | 3 |
| **K- 07 10 09 57** | G 3/8 male | 50,0 | 10 | aluminij | 4 |
| **K- 07 10 09 58** | G 1/4 male | 41,0 | 13 | aluminij | 5 |
| **K- 07 10 09 59** | G 1/4 male | 46,0 | 17 | Die cast zinc | 6 |
| **K- 07 10 11 14** | G 1/4 male | 40,0 | 17 | Plastic (POM) | 7 |
| **K- 07 10 11 15** | G 1/4 male | 35,0 | 11 | aluminij | 8 |
| **K- 07 10 11 16** | G 1/4 male | 47,0 | 19 | Die cast zinc | 9 |
| **K- 07 10 11 17** | G 1/4 male | 55,0 | 19 | Plastic (ABS) | 10 |

*Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.*