K-ENDLAGEN-RUECKME KUNST S

End position feedback plastic- inductive sensors

Lastnosti

delovni tok	200 mA
vijačna pritrditev kabla	M 20 x 1.5
preklopna funkcija	Positive switching, PNP NO contact, damped or undamped in the end position
razred zaščite	IP 67, acc. to DIN EN 60529
območje temperatur:	-20 °C to +70 °C
ohišje	Polyamide blue or black
vijak	Stainless steel 1.4301
gred	Polyamide PA6, black
pokrov	Polycarbonate, transparent
montažni most	PA6 with 30 % glass fibre
tesnila	EPDM and NBR
tesnilni material	NBR



Navodilo

Drugi podatki na zahtevo.

Opis

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

Artikel

Opis	Napetost	definicija
K- 07 30 29 06	9 V - 36 V DC	End position feedback, D 2 type with inductive 3-wire sensors

Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.