

# K-FI REGL PC-BEHÄLTER S V HW G

Filter regulators with polycarbonate bowl, bowl guard and »HW« mounting bracket, fully-automatic drain valve

**HANSA FLEX**

## Lastnosti

|                                  |  |
|----------------------------------|--|
| vstopni tlak                     | Max. 10 bar  |
| temperatura medija               | max. 70 °C   |
| temperatura okolice              | Max. 70 °C   |
| velikost por v filtrnem elementu | 5 µm   |
| tesnilni material                | NBR  |
| vzmetni pokrov                   | POM  |
| ohišje                           | Die-cast aluminium   |
| Drain valve                      | Semi- or fully-automatic                                       |
| meritev pretoka                  | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| drugi podatki                    | User manual on request   |



## Artikel

| Opis           | Navoj | regulacijsko območje | pretok (L/min) | A (mm) | B        | C (mm) | D (mm) | Velikost |
|----------------|-------|----------------------|----------------|--------|----------|--------|--------|----------|
| K- 07 25 06 96 | G 1/4 | 1.5 - 9 bar          | 1450           | 51,0   | 225,5 mm | 82,5   | 143,0  | 300      |
| K- 07 25 06 98 | G 3/8 | 1.5 - 9 bar          | 1750           | 51,0   | 225,5 mm | 82,5   | 143,0  | 300      |
| K- 07 25 07 00 | G 1/2 | 1.5 - 9 bar          | 1750           | 51,0   | 225,5 mm | 82,5   | 143,0  | 300      |
| K- 07 25 07 02 | G 3/8 | 1.5 - 9 bar          | 3750           | 68,0   | 270,5 mm | 104,0  | 166,5  | 400      |
| K- 07 25 07 04 | G 1/2 | 1.5 - 9 bar          | 3750           | 68,0   | 270,5 mm | 104,0  | 166,5  | 400      |

## Pribor

|                                    |   |
|------------------------------------|---|
| K-VERSCHLEI-SATZ                   | Set of wearing parts                                    |
| K-ERSATZMEMBRANE                   | Replacement diaphragm                                   |
| K-ADAPTERPLATTEN HANSA             | Adapter plate HANSA                                     |
| K-ERSATZBEHÄLTER G UND G-MINI POLY | Spare tanks »G« Series and »G-mini« Series Polycarbonat |
| K-SCHUTZKORB G                     | Protective cage   |
| K-FILTERELEMENT                    | Filter element  |
| K-HALTERBAUSATZ                    | Holder  |
| K-VERBINDUNGSELEMENTE              | Connecting sets   |
| K-WANDHALTER                       | Wall bracket  |