

# K-ENDVERTEILERDOSEN

End porting box without through-hole thread, PN 15

**HANSA FLEX**

## Lastnosti

Obratovalni tlak	Max. 15 bar
pritezni moment	4 Nm
pritezni moment navoja MS	12 Nm
območje temperatur:	-10 °C to +50 °C
ohišje	Glass fibre-reinforced plastic
navoj	Brass



## Navodilo

Drugi podatki na zahtevo.

## Opis

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

## Artikel

Opis	Navoj vhod	Priključni navoj
K- 07 40 48 12	G 1/2"	1 x G 1/2
K- 07 40 48 13	G 1/2"	2 x G 1/2
K- 07 40 48 14	G 1/2"	3 x G 1/2
K- 07 40 48 15	G 3/4"	1 x G 1/2
K- 07 40 48 16	G 3/4"	2 x G 1/2
K- 07 40 48 17	G 3/4"	3 x G 1/2