

# K-ENDVERTEILERDOSEN

End porting box without through-hole thread, PN 15

**HANSA FLEX**

## Lastnosti

|                           |                                |
|---------------------------|--------------------------------|
| Obratovalni tlak          | Max. 15 bar                    |
| pritezni moment           | 4 Nm                           |
| pritezni moment navoja MS | 12 Nm                          |
| območje temperatur:       | -10 °C to +50 °C               |
| ohišje                    | Glass fibre-reinforced plastic |
| navoj                     | Brass                          |



## Navodilo

Drugi podatki na zahtevo.

## Opis

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

## Artikel

| Opis           | Navoj vhod | Priključni navoj |
|----------------|------------|------------------|
| K- 07 40 48 12 | G 1/2"     | 1 x G 1/2        |
| K- 07 40 48 13 | G 1/2"     | 2 x G 1/2        |
| K- 07 40 48 14 | G 1/2"     | 3 x G 1/2        |
| K- 07 40 48 15 | G 3/4"     | 1 x G 1/2        |
| K- 07 40 48 16 | G 3/4"     | 2 x G 1/2        |
| K- 07 40 48 17 | G 3/4"     | 3 x G 1/2        |