

# K-SCHUTZROHRE EINSCHRAUB

Screw-in thermowells

**HANSA FLEX**

## Lastnosti

Obratovalni tlak	Max. 6 bar (copper alloy), Max. 25 bar (stainless steel)
Ø tesnilnega stika	26 mm
Ø zaščitne cevi	10 mm
Material:	Copper alloy, CrNi-Steel 1.4571



## Navodilo

Drugi podatki na zahtevo.

## Opis

For bimetallic thermometers in the »High quality« series.

## Artikel

Opis	Priključni navoj	vgradna dolžina	SW (mm)	Material:
K- 07 20 11 35	G 1/2	L1 = 63 mm	27	Copper alloy
K- 07 20 11 36	G 1/2	L1 = 100 mm	27	Copper alloy
K- 07 20 11 37	G 1/2	L1 = 160 mm	27	Copper alloy
K- 07 20 11 38	G 1/2	L1 = 63 mm	27	CrNi steel 1.4571
K- 07 20 11 39	G 1/2	L1 = 100 mm	27	CrNi steel 1.4571
K- 07 20 11 40	G 1/2	L1 = 160 mm	27	CrNi steel 1.4571

## Pribor

K-BIMETALLTHERMOMETER 52-2 Bimetallic thermometers