

K-DRS WECHSELKONTAK ANFLANSCHBAR DS

Pressure switches, changeover type, suitable for flange mounting
K-07302861

HANSA FLEX

Lastnosti

Način izdelave	Spring-loaded diaphragm (NBR)
Območje uporabe	Air, neutral gases (lubricated or unlubricated)
temperatura okolice	-10 °C to +60 °C
Električni priključek	Pg 11P coupling plug, acc. to ISO 4400
pogostost preklapljanja	60/min.
napetost preklopa	max. 250 V AC/DC
funkcija	Changeover
razred zaščite	IP 65
Material:	Plastic Grivory (PA 61/XT)



Navodilo

Drugi podatki na zahtevo.

Opis

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

Artikel

Opis	območje nastavitve
------	--------------------

K- 07 30 28 61	0,5 - 10,0 bar
----------------	----------------

je pribor za naslednje izdelke

K-VT SCHMAL MULTIFIX	Manifolds - narrow design
----------------------	---------------------------

K-VT BREIT MULTIFIX	Manifolds - wide design
---------------------	-------------------------

je nadomestni del za naslednje izdelke

K-VERTEILER HANSA	Manifolds
-------------------	-----------