

# K-SCHOTT-STECKVERB VA

Female bulkhead connectors

**HANSA FLEX**

## Lastnosti

|                        |   |
|------------------------|---|
| impulzni delovni tlak  | Max. 10 bar   |
| tlak                   | Max. 15 bar (depending on pipe quality)                         |
| primeren material cevi | PVDF, PTFE, stainless steel, PA, PU                             |
| Standard               | G thread acc. to DIN EN ISO 228-1                               |
| temperatura okolice    | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Material:              | legirano jeklo 1.4404   |
| tesnilni material      | FKM   |



## Navodilo

Drugi podatki na zahtevo.

## Opis

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Artikel

| Opis           | Navoj      | za zunanji Ø mm cevi | L1 (mm) | zev ključa |
|----------------|------------|----------------------|---------|------------|
| K- 07 40 24 30 | M 12 x 1.0 | 4 mm                 | 28,0    | 15 mm      |
| K- 07 40 24 31 | M 14 x 1.0 | 6 mm                 | 34,4    | 17 mm      |
| K- 07 40 24 32 | M 16 x 1.0 | 8 mm                 | 34,5    | 19 mm      |
| K- 07 40 24 33 | M 18 x 1.0 | 10 mm                | 38,6    | 21 mm      |
| K- 07 40 24 34 | M 20 x 1.0 | 12 mm                | 40,8    | 24 mm      |