


K-XVMK 5

Male connectors, conical male thread acc. to ISO 7-1, stainless steel

HANSA FLEX

Lastnosti

tlačno območje	Max. 25 bar
priporočene cevi	PTFE hose
območje temperatur:	-40 °C to +200 °C (depending on the hose quality and diameter)
Material:	legirano jeklo 1.4404
tesnilo	Pure metal



Navodilo

Drugi podatki na zahtevo.

Opis

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Artikel

Opis	Navoj	za cev	L1 (mm)	zev ključa 1 (mm)	zev ključa 2 (mm)
K- 07 40 30 19	R 1/8	6 mm / 4 mm	26,0	12	10
K- 07 40 30 20	R 1/8	8 mm / 6 mm	26,5	14	13
K- 07 40 30 17	R 1/4	6 mm / 4 mm	29,5	12	14
K- 07 40 30 18	R 1/4	8 mm / 6 mm	30,0	14	14
K- 07 40 30 16	R 1/4	10 mm / 8 mm	32,5	16	14
K- 07 40 30 21	R 3/8	10 mm / 8 mm	33,0	16	17