K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

Lastnosti

Sredstva	Air, neutral gases, filtered
delovni tlak	0.5 to 10 bar
delovna temperatura	-20 °C to +70 °C
v obsegu dobave	1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws
ohišje	Aluminium, anodised
Material:	Tesnilo: NBR
tesnilni material	NBR



Navodilo

Drugi podatki na zahtevo.

Opis

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

Artikel

Opis	funkcija	sprožitev	DN	pretok (L/min)
K- 07 15 22 39	3/2-way	Knurled Screw	5	650
K- 07 15 22 40	3/2-way	Screwdriver	5	650
K- 07 15 22 41	5/2-way	Knurled Screw	5	650
K- 07 15 22 42	5/2-way	Screwdriver	5	650

Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.