K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

Lastnosti

Sredstva	Filtered, unlubricated compressed air
Obratovalni tlak	2.5 - 8 bar
območje temperatur:	-10 °C to +60 °C
Priključek	Push-in fitting for pipe 4 mm
sprožitev	Pneumatic
pretok zraka 6 bar	85 Nl/min
maks. časovni zamik vhodnega signala	0,4 s



Navodilo

Drugi podatki na zahtevo.

Opis

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter.Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Artikel

Opis	definicija	Priključek
K- 07 15 26 09	Two-hand safety valve without housing	Push-in fitting for 4 mm pipe
K- 07 15 26 10	mounting element	-

Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.