

K-DMUF 1

Pressure transmitters (CrNi steel 1.4404)

HANSA FLEX

Lastnosti

| | |
|--------------------------------------|--|
| tip | A-10 |
| napetost | 8 - 30 V |
| Električni priključek | With right-angle connector acc. to DIN EN 175301-803 A |
| razred zaščite | IP 65 acc. to EN 60529 |
| izhodni signal | 4 to 20 mA, 2-wire |
| nelinearnost | 0.5% of span |
| temperatura medija | 0 °C to +80 °C |
| temperatura okolice | 0 °C to +80 °C |
| deli, ki so v stiku z merjeno snovjo | CrNi steel 1.4404 |
| ohišje | CrNi steel 1.4404 |



Navodilo

Drugi podatki na zahtevo.

Opis

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

Dodatne informacije

Further measuring ranges on request

Pressure converter with output signal 0 - 10 V, 0 - 5 V and others on request.

Artikel

| Opis | Mersko območje | Navoj |
|----------------|----------------|-------|
| K- 07 20 10 46 | 0 - 1.0 bar | G 1/4 |
| K- 07 20 10 47 | 0 - 1.6 bar | G 1/4 |
| K- 07 20 10 48 | 0 - 2.5 bar | G 1/4 |
| K- 07 20 10 49 | 0 - 4.0 bar | G 1/4 |
| K- 07 20 10 50 | 0 - 6.0 bar | G 1/4 |
| K- 07 20 10 51 | 0 - 10.0 bar | G 1/4 |
| K- 07 20 10 52 | 0 - 16.0 bar | G 1/4 |
| K- 07 20 10 53 | 0 - 25.0 bar | G 1/4 |
| K- 07 20 10 54 | 0 - 40.0 bar | G 1/4 |
| K- 07 20 10 55 | 0 - 60.0 bar | G 1/4 |
| K- 07 20 10 56 | 0 - 100.0 bar | G 1/4 |
| K- 07 20 10 57 | 0 - 160.0 bar | G 1/4 |
| K- 07 20 10 58 | 0 - 250.0 bar | G 1/4 |
| K- 07 20 10 59 | 0 - 400.0 bar | G 1/4 |
| K- 07 20 10 60 | 0 - 600.0 bar | G 1/4 |