

K-TUE 7,2 7,8 MS NI

Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass

HANSA FLEX

Lastnosti

| | |
|--------------------|---|
| Obratovalni tlak | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| temperatura medija | -20 °C to +100 °C |
| Material: | ponikljana medenina |



Navodilo

Drugi podatki na zahtevo.

Artikel

| Opis | definicija |
|----------------|---------------|
| K- 07 35 01 76 | Stem, I.D. 6 |
| K- 07 35 01 88 | Stem, I.D. 8 |
| K- 07 35 01 77 | Stem, I.D. 9 |
| K- 07 35 01 89 | Stem, I.D. 10 |
| K- 07 35 01 84 | Stem, I.D. 13 |

je dodatni del za naslednje izdelke

| | |
|--------------------------|---|
| K-SVKM NW 7,8 AG H | Quick disconnect couplings DN 7.8 - for extremely high flow rates, male |
| K-SVKM NW 7,8 IG H | Quick disconnect couplings DN 7.8 - for extremely high flow rates, female |
| K-SVKM NW 7,8 SCHL TUE H | Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem |
| K-LKM S NW7,8 AG | Safety couplings DN 7.8, male |
| K-LKM S NW7,8 IG | Safety couplings DN 7.8, female |
| K-LKM S NW7,8 SCHL TUE | Safety couplings DN 7.8, with hose stem |