


# K-NIPPEL KUPPL NW7 IG MS NI

Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female

**HANSA FLEX**

## Lastnosti

Obratovalni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
temperatura medija	-20 °C to +100 °C
Material:	ponikljana medenina



## Navodilo

Drugi podatki na zahtevo.

## Artikel

Opis	definicija	SW (mm)
K- 07 35 01 96	Plug G 1/8 female	14
K- 07 35 01 97	Plug G 1/4 female	17
K- 07 35 01 98	Plug G 3/8 female	19
K- 07 35 01 99	Plug G 1/2 female	24

## je dodatni del za naslednje izdelke

K-SVKM NW 7,8 AG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, male
K-SVKM NW 7,8 IG H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, female
K-SVKM NW 7,8 SCHL TUE H	Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem
K-LKM S NW7,8 AG	Safety couplings DN 7.8, male
K-LKM S NW7,8 IG	Safety couplings DN 7.8, female
K-LKM S NW7,8 SCHL TUE	Safety couplings DN 7.8, with hose stem