

# K-SVKM NW 7,2 SCHL-TUE VA

Quick disconnect couplings DN 7.2, stainless steel, with hose stem

**HANSA FLEX**

## Lastnosti

Obratovalni tlak	1 - 35 bar and rough vacuum
pretok zraka	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
temperatura medija	-25 °C to +200 °C
ohišje, puša, ohišje ventila	Stainless steel 1.4305
vzmet, notranji zaskočnik	Stainless steel 1.4310
blokirni zatiči	Stainless steel 1.4401
tesnilni material	FKM



## Navodilo

Drugi podatki na zahtevo.

## Opis

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

## Artikel

Opis	Priključek	dolžina (mm)	SW (mm)
K- 07 35 07 65	Stem, I.D. 6	59,0	22
K- 07 35 12 65	Stem, I.D. 8	59,0	22
K- 07 35 07 66	Stem, I.D. 9	59,0	22
K- 07 35 12 66	Stem, I.D. 10	59,0	22
K- 07 35 07 67	Stem, I.D. 13	59,0	22

## Dodatni elementi

K-NIPPEL KUPPL NW7 AG VA 2	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male
K-NIPPEL KUPPL NW7 IG VA 1	Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female
K-TUE 7,2 7,8 VA 2	Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305