

K-SVKM NW 7,8 AG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, male

HANSA FLEX

Lastnosti

Obratovalni tlak	0 - 35 bar
pretok zraka	2.100 l/min (at $\Delta p = 0.5$ bar)
temperatura medija	-20 °C to +40 °C
navojni kos	Nickel-plated brass
ohišje ventila	Steel, QPQ treated
puša za deblokado	Extremely robust, ergonomic plastic
ventil, sedež	Brass
Sredstva	Only for clean compressed air
tesnila	NBR
vzmet, notranji zaskočnik, krogle	stain less steel



Navodilo

Drugi podatki na zahtevo.

Opis

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Artikel

Opis	Priključek	dolžina (mm)	SW (mm)
K- 07 35 08 47	G 1/4 male	65,0	19
K- 07 35 08 48	G 3/8 male	65,0	19
K- 07 35 08 49	G 1/2 male	59,0	22

Dodatni elementi

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass