

# K-SVKM NW 7,8 IG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, female

**HANSA FLEX**

## Lastnosti

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Obratovalni tlak                  | 0 - 35 bar                            |
| pretok zraka                      | 2.100 l/min (at $\Delta p = 0.5$ bar) |
| temperatura medija                | -20 °C to +40 °C                      |
| navojni kos                       | Nickel-plated brass                   |
| ohišje ventila                    | Steel, QPQ treated                    |
| puša za deblokado                 | Extremely robust, ergonomic plastic   |
| ventil, sedež                     | Brass                                 |
| Sredstva                          | Only for clean compressed air         |
| tesnila                           | NBR                                   |
| vzmet, notranji zaskočnik, krogle | stain less steel                      |



## Navodilo

Drugi podatki na zahtevo.

## Opis

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

## Artikel

| Opis           | Priključek   | dolžina<br>(mm) | SW<br>(mm) |
|----------------|--------------|-----------------|------------|
| K- 07 35 08 50 | G 1/4 female | 59,0            | 19         |
| K- 07 35 08 51 | G 3/8 female | 59,0            | 19         |
| K- 07 35 08 52 | G 1/2 female | 62,0            | 24         |

## Dodatni elementi

|                               |  |
|-------------------------------|--|
| K-NIPP KUPPL NW7 SCHL MS NI K | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring |
| K-NIPPEL KUPPL NW7 AG MS NI   | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male   |
| K-NIPPEL KUPPL NW7 IG MS NI   | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female   |
| K-NIPPEL KUPPL NW7 SCHL MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose   |
| K-TUE 7,2 7,8 MS NI           | Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass   |