

K-TUE 7,2 7,8 VA 1

Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305

HANSA FLEX

Lastnosti

| | |
|------------------|---|
| Obratovalni tlak | maks. 10 bar |
| pretok zraka | 1.800 l/min (at 6 bar and $\Delta p = 1$ bar) |
| Material: | stainless steel 1.4305 |



Artikel

| Opis | definicija |
|----------------|---------------|
| K- 07 35 02 58 | Stem, I.D. 6 |
| K- 07 35 02 59 | Stem, I.D. 8 |
| K- 07 35 02 60 | Stem, I.D. 9 |
| K- 07 35 02 61 | Stem, I.D. 10 |
| K- 07 35 02 62 | Stem, I.D. 13 |

je dodatni del za naslednje izdelke

| | |
|---------------------------|---|
| K-SVKM NW 7,8 AG VA | Quick disconnect couplings DN 7.8, stainless steel 1.4305, male |
| K-SVKM NW 7,8 IG VA | Quick disconnect couplings DN 7.8, stainless steel 1.4305, female |
| K-SVKM NW 7,8 SCHL TUE VA | Quick disconnect couplings DN 7.8, stainless steel 1.4305, with hose stem |