

K-KOMP ZYL DOPPELW IG

Compact cylinders, double-acting (with magnet), non-cushioned, female piston rod

HANSA FLEX

Lastnosti

| | |
|----------------------------|---|
| Sredstva | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| delovni tlak | Max. 10 bar |
| vklopni tlak | 0,6 bar (Ø 20 bis Ø 32), 0,4 bar (Ø 40 bis Ø 100) |
| območje temperatur: | -10 °C to +60 °C (Ø 20 to Ø 63) -10 °C to +80 °C (Ø 80 bis Ø 100) |
| batnica | C45 steel, hard chrome-plated |
| cev | Anodised aluminium jacket with T-slots |
| bat | POM (Ø 20 to Ø 63); Aluminium (Ø 80 to Ø 100) |
| tesnilni material | NBR |



Navodilo

Drugi podatki na zahtevo.

Opis

New series acc. to ISO 21287 characterised by a very short and compact design. The standard type features a magnetic piston. Piston rod optionally with male or female thread.

Artikel

| Opis | Ø bata | Hod (mm) | Priključek | navoj znotraj batnica |
|----------------|--------|----------|------------|-----------------------|
| K- 07 15 08 87 | 20 mm | 5 | M 5 | M 6 |
| K- 07 15 08 88 | 20 mm | 10 | M 5 | M 6 |
| K- 07 15 08 89 | 20 mm | 15 | M 5 | M 6 |
| K- 07 15 08 90 | 20 mm | 20 | M 5 | M 6 |
| K- 07 15 08 91 | 20 mm | 25 | M 5 | M 6 |
| K- 07 15 08 92 | 20 mm | 30 | M 5 | M 6 |
| K- 07 15 08 93 | 20 mm | 40 | M 5 | M 6 |
| K- 07 15 08 94 | 20 mm | 50 | M 5 | M 6 |
| K- 07 15 08 95 | 20 mm | 60 | M 5 | M 6 |
| K- 07 15 08 96 | 25 mm | 5 | M 5 | M 6 |
| K- 07 15 08 97 | 25 mm | 10 | M 5 | M 6 |
| K- 07 15 08 98 | 25 mm | 15 | M 5 | M 6 |
| K- 07 15 08 99 | 25 mm | 20 | M 5 | M 6 |
| K- 07 15 09 00 | 25 mm | 25 | M 5 | M 6 |
| K- 07 15 09 01 | 25 mm | 30 | M 5 | M 6 |
| K- 07 15 09 02 | 25 mm | 40 | M 5 | M 6 |
| K- 07 15 09 03 | 25 mm | 50 | M 5 | M 6 |
| K- 07 15 09 04 | 25 mm | 60 | M 5 | M 6 |
| K- 07 15 09 05 | 32 mm | 5 | G 1/8 | M 8 |
| K- 07 15 09 06 | 32 mm | 10 | G 1/8 | M 8 |
| K- 07 15 09 07 | 32 mm | 15 | G 1/8 | M 8 |
| K- 07 15 09 08 | 32 mm | 20 | G 1/8 | M 8 |
| K- 07 15 09 09 | 32 mm | 25 | G 1/8 | M 8 |
| K- 07 15 09 10 | 32 mm | 30 | G 1/8 | M 8 |
| K- 07 15 09 11 | 32 mm | 40 | G 1/8 | M 8 |
| K- 07 15 09 12 | 32 mm | 50 | G 1/8 | M 8 |
| K- 07 15 09 13 | 32 mm | 60 | G 1/8 | M 8 |
| K- 07 15 09 14 | 32 mm | 80 | G 1/8 | M 8 |
| K- 07 15 09 15 | 40 mm | 5 | G 1/8 | M 8 |
| K- 07 15 09 16 | 40 mm | 10 | G 1/8 | M 8 |
| K- 07 15 09 17 | 40 mm | 15 | G 1/8 | M 8 |
| K- 07 15 09 18 | 40 mm | 20 | G 1/8 | M 8 |
| K- 07 15 09 19 | 40 mm | 25 | G 1/8 | M 8 |
| K- 07 15 09 20 | 40 mm | 30 | G 1/8 | M 8 |
| K- 07 15 09 21 | 40 mm | 40 | G 1/8 | M 8 |
| K- 07 15 09 22 | 40 mm | 50 | G 1/8 | M 8 |
| K- 07 15 09 23 | 40 mm | 60 | G 1/8 | M 8 |
| K- 07 15 09 24 | 40 mm | 80 | G 1/8 | M 8 |
| K- 07 15 09 25 | 50 mm | 5 | G 1/8 | M 10 |



Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.

06.06.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-KOMP ZYL DOPPELW IG

Compact cylinders, double-acting (with magnet), non-cushioned, female piston rod

HANSA FLEX

| Artikel | | | | |
|----------------|--------|----------|------------|-----------------------|
| Opis | Ø bata | Hod (mm) | Priključek | navoj znotraj batnica |
| K- 07 15 09 26 | 50 mm | 10 | G 1/8 | M 10 |
| K- 07 15 09 27 | 50 mm | 15 | G 1/8 | M 10 |
| K- 07 15 09 28 | 50 mm | 20 | G 1/8 | M 10 |
| K- 07 15 09 29 | 50 mm | 25 | G 1/8 | M 10 |
| K- 07 15 09 30 | 50 mm | 30 | G 1/8 | M 10 |
| K- 07 15 09 31 | 50 mm | 40 | G 1/8 | M 10 |
| K- 07 15 09 32 | 50 mm | 50 | G 1/8 | M 10 |
| K- 07 15 09 33 | 50 mm | 60 | G 1/8 | M 10 |
| K- 07 15 09 34 | 50 mm | 80 | G 1/8 | M 10 |
| K- 07 15 09 35 | 63 mm | 5 | G 1/8 | M 10 |
| K- 07 15 09 36 | 63 mm | 10 | G 1/8 | M 10 |
| K- 07 15 09 37 | 63 mm | 15 | G 1/8 | M 10 |
| K- 07 15 09 38 | 63 mm | 20 | G 1/8 | M 10 |
| K- 07 15 09 39 | 63 mm | 25 | G 1/8 | M 10 |
| K- 07 15 09 40 | 63 mm | 30 | G 1/8 | M 10 |
| K- 07 15 09 41 | 63 mm | 40 | G 1/8 | M 10 |
| K- 07 15 09 42 | 63 mm | 50 | G 1/8 | M 10 |
| K- 07 15 09 43 | 63 mm | 60 | G 1/8 | M 10 |
| K- 07 15 09 44 | 63 mm | 80 | G 1/8 | M 10 |
| K- 07 15 09 45 | 80 mm | 5 | G 1/8 | M 12 |
| K- 07 15 09 46 | 80 mm | 10 | G 1/8 | M 12 |
| K- 07 15 09 47 | 80 mm | 15 | G 1/8 | M 12 |
| K- 07 15 09 48 | 80 mm | 20 | G 1/8 | M 12 |
| K- 07 15 09 49 | 80 mm | 25 | G 1/8 | M 12 |
| K- 07 15 09 50 | 80 mm | 30 | G 1/8 | M 12 |
| K- 07 15 09 51 | 80 mm | 40 | G 1/8 | M 12 |
| K- 07 15 09 52 | 80 mm | 50 | G 1/8 | M 12 |
| K- 07 15 09 53 | 80 mm | 60 | G 1/8 | M 12 |
| K- 07 15 09 54 | 80 mm | 80 | G 1/8 | M 12 |
| K- 07 15 08 77 | 100 mm | 5 | G 1/8 | M 12 |
| K- 07 15 08 78 | 100 mm | 10 | G 1/8 | M 12 |
| K- 07 15 08 79 | 100 mm | 15 | G 1/8 | M 12 |
| K- 07 15 08 80 | 100 mm | 20 | G 1/8 | M 12 |
| K- 07 15 08 81 | 100 mm | 25 | G 1/8 | M 12 |
| K- 07 15 08 82 | 100 mm | 30 | G 1/8 | M 12 |
| K- 07 15 08 83 | 100 mm | 40 | G 1/8 | M 12 |
| K- 07 15 08 84 | 100 mm | 50 | G 1/8 | M 12 |
| K- 07 15 08 85 | 100 mm | 60 | G 1/8 | M 12 |
| K- 07 15 08 86 | 100 mm | 80 | G 1/8 | M 12 |