


# K-SSVKM NW 5 SCHL TUE MS BL

Quick disconnect couplings DN 5, brass with a bare metal surface, with bulkhead fitting and hose stem

**HANSA FLEX**

## Lastnosti

Obratovalni tlak	0 - 35 bar, maximum static working pressure (non-pulsating)
pretok zraka	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
temperatura medija	-20 °C to +100 °C
ohišje, puša, ohišje ventila	Brass
vzmet, notranji zaskočnik, krogle	Stainless steel
tesnilni material	NBR



## Navodilo

Drugi podatki na zahtevo.

## Opis

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

## Artikel

Opis	Priključek	dolžina (mm)	Pregradni navoj	SW (mm)
K- 07 35 06 45	Stem, I.D. 4	60,0	M 10 x 1	14
K- 07 35 06 46	Stem, I.D. 6	60,0	M 12 x 1	17
K- 07 35 06 47	Stem, I.D. 9	60,0	M 12 x 1	17