


# K-VENTILSCHEIBE HDM 8

Valve discs for HDM valve terminal with 8 mm port

**HANSA FLEX**

## Lastnosti

|                                |   |
|--------------------------------|---|
| <b>Sredstva</b>                | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| <b>delovni tlak</b>            | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)                      |
| <b>krmilni tlak</b>            | 3 - 7 bar   |
| <b>območje temperatur:</b>     | -10 °C to +60 °C  |
| <b>pretok</b>                  | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)  |
| <b>število krmilnikov</b>      | Max. 16 (e.g. 16 spring return valves)  |
| <b>pomožna ročna sprožitve</b> | Latching (bistable), Monostable (non-latching) version also available on request                    |
| <b>potrebna moč</b>            | 0.6 W per pilot   |
| <b>razred zaščite</b>          | IP 65   |



## Navodilo

Drugi podatki na zahtevo.

## Opis

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

## Artikel

| Opis           | funkcija   |
|----------------|--|
| K- 07 15 20 69 | 2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted   |
| K- 07 15 20 72 | 2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised |
| K- 07 15 20 63 | 3/2-way, NC, monostable and 3/2-way, NO, monostable              |
| K- 07 15 20 71 | 5/2-way, monostable  |
| K- 07 15 20 68 | 5/2-way, monostable (uses only one pin, two signals assigned)    |
| K- 07 15 20 70 | 5/2-way, bistable (pulse valve)                                  |
| K- 07 15 20 65 | 5/3-way, mid-position closed                                     |