

K-STECKNIPPEL RED

push-in plugs, unequal

HANSA FLEX

Lastnosti

| | |
|---------------------|--|
| delovni tlak | Max. 15 bar, coarse vacuum |
| Območje uporabe | Air, vacuum |
| priporočene cevi | PU or PA (nylon) |
| Sredstva | Compressed air and all gases or liquids that are compatible with the materials |
| območje temperatur: | -20 °C to +80 °C |
| tesnilna ploskev | Parallel version: O-ring in housing, Conical version: thread coating |
| Material: | Plastic, Nickel plated brass |
| potisni obroč | Plastic |



Navodilo

Drugi podatki na zahtevo.

Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artikel

| Opis | za zunanji Ø mm cevi | L1 (mm) |
|----------------|----------------------|---------|
| K- 07 40 42 83 | 6 mm / 4 mm | 37,5 |
| K- 07 40 42 84 | 8 mm / 4 mm | 40,5 |
| K- 07 40 42 85 | 8 mm / 6 mm | 42,5 |
| K- 07 40 42 86 | 10 mm / 6 mm | 44,5 |
| K- 07 40 42 87 | 10 mm / 8 mm | 47,0 |
| K- 07 40 42 88 | 12 mm / 8 mm | 49,5 |
| K- 07 40 42 89 | 12 mm / 10 mm | 51,0 |