



K-T-STECK VERS DRE AG-K BE 1

Male branch tees, swivel type, conical male thread, coated

HANSA FLEX

Lastnosti

delovni tlak	Max. 16 bar
delovna temperatura	-20 °C to +150 °C
Material:	ponikljana medenina
potisni obroč	Nickel-plated brass
vpenjalni obroč	Stainless steel



Navodilo

Drugi podatki na zahtevo.

Opis

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Artikel

Opis	Navoj	za zunanji Ø mm cevi	L1 (mm)	L2 (mm)	zev ključa
K- 07 40 28 18	R 1/8	4 mm	40,0	20,0	13 mm
K- 07 40 28 19	R 1/8	6 mm	43,0	20,0	13 mm
K- 07 40 28 20	R 1/8	8 mm	47,0	20,0	13 mm
K- 07 40 28 16	R 1/4	6 mm	43,0	25,0	14 mm
K- 07 40 28 17	R 1/4	8 mm	47,0	25,0	14 mm
K- 07 40 28 15	R 1/4	10 mm	53,0	26,0	16 mm
K- 07 40 28 21	R 3/8	8 mm	47,0	28,0	18 mm
K- 07 40 48 02	R 3/8	10 mm	53,0	30,0	18 mm
K- 07 40 48 03	R 3/8	12 mm	58,0	32,5	20 mm
K- 07 40 48 01	R 1/2	12 mm	58,0	35,5	22 mm