

# K-W90 SVB POLYPROPYLEN

Bulkhead elbow couplings - polypropylene

**HANSA FLEX**

## Lastnosti

|                            |   |
|----------------------------|---|
| <b>Obratovalni tlak</b>    | Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 2.5 bar (at 90 °C) |
| <b>Material:</b>           | Polypropylene (PP)  |
| <b>delovna temperatura</b> | Max. 90 °C  |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Chemically resistant to almost all inorganic acids and bases, even in high concentrations and at temperatures greater than 90 °C.

## Artikel

| Opis           | za cev       | Navoj      | L1 (mm) | L2 (mm) | zav ključa |
|----------------|--------------|------------|---------|---------|------------|
| K- 07 40 41 75 | 4 mm / 6 mm  | M 10 x 1   | 43,0    | 25,0    | 14 mm      |
| K- 07 40 41 76 | 6 mm / 8 mm  | M 14 x 1,5 | 53,0    | 33,0    | 19 mm      |
| K- 07 40 41 77 | 8 mm / 10 mm | M 16 x 1,5 | 58,0    | 36,0    | 22 mm      |
| K- 07 40 41 78 | 9 mm / 12 mm | M 18 x 1,5 | 67,0    | 43,0    | 24 mm      |