

K-DV GEW B RAENDEL

Bidirectional flow control valves, air restriction at both ends (»B«), screw connection

HANSA FLEX

Lastnosti

| | |
|---|------------------------------------|
| Obratovalni tlak | maks. 10 bar |
| območje temperatur: | 0 °C to +70 °C |
| votli vijak, vrtljiva ročica, regulirni vijak | Nickel-plated brass |
| notranji deli | Brass with a bare metal surface |
| tesnilo z zavahkom tesnilnega obroča | NBR |
| tesnila (neizgubljiva) | Polyamide (glass fibre-reinforced) |



Navodilo

Drugi podatki na zahtevo.

Opis

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly.
On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Artikel

| Opis | Priključek | C (mm) | Navoj | zev ključa | B (mm) |
|----------------|---------------------|--------|-------|------------|--------|
| K- 07 15 25 16 | M 5 female thread | 11,5 | M 5 | 8 mm | 38,9 |
| K- 07 15 04 97 | G 1/8 female thread | 16,0 | G 1/8 | 14 mm | 42,0 |
| K- 07 15 04 93 | G 1/4 female thread | 22,0 | G 1/4 | 17 mm | 51,0 |
| K- 07 15 25 17 | G 1/2 female thread | 32,0 | G 1/2 | 26 mm | 81,0 |
| K- 07 15 25 18 | G 3/8 female thread | 26,0 | G 3/8 | 20 mm | 63,0 |