


K-L-STECKVER DREH AG OR VA

Male elbows, swivel type, parallel male thread with O-ring

HANSA FLEX

Lastnosti

| | |
|------------------------|---|
| impulzni delovni tlak | Max. 10 bar |
| tlak | Max. 15 bar (depending on pipe quality) |
| primeren material cevi | PVDF, PTFE, stainless steel, PA, PU |
| Standard | G thread acc. to DIN EN ISO 228-1, with O-Ring |
| temperatura okolice | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Material: | legirano jeklo 1.4404 |
| tesnilni material | FKM |



Navodilo

Drugi podatki na zahtevo.

Opis

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Artikel

| Opis | Navoj | za zunanji Ø mm cevi | L1 (mm) | L2 (mm) | zev ključa |
|----------------|-------|----------------------|---------|---------|------------|
| K- 07 40 46 76 | M 5 | 4 mm | 17,0 | 14,0 | 9 mm |
| K- 07 40 23 91 | G 1/8 | 4 mm | 17,0 | 16,0 | 13 mm |
| K- 07 40 23 93 | G 1/8 | 8 mm | 22,0 | 18,0 | 13 mm |
| K- 07 40 23 92 | G 1/8 | 6 mm | 21,5 | 18,0 | 13 mm |
| K- 07 40 23 89 | G 1/4 | 6 mm | 21,5 | 20,0 | 16 mm |
| K- 07 40 23 90 | G 1/4 | 8 mm | 22,0 | 20,0 | 16 mm |
| K- 07 40 23 88 | G 1/4 | 10 mm | 25,5 | 22,5 | 16 mm |
| K- 07 40 23 94 | G 3/8 | 10 mm | 25,5 | 24,0 | 21 mm |
| K- 07 40 23 95 | G 3/8 | 12 mm | 28,0 | 26,5 | 21 mm |
| K- 07 40 23 87 | G 1/2 | 12 mm | 28,0 | 31,0 | 22 mm |