

K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick disconnect couplings and stems DN 7.2

HANSA FLEX

Lastnosti

Notranja plast	Soft-PVC, black
Vloga	poliestrska pletenina
Zunanja plast	Soft-PVC, blue
delovna temperatura	-20 °C to +60 °C



Navodilo

Drugi podatki na zahtevo.

Opis

Highly flexible hose for compressed air applications in workshop areas. Assembled with brass stem and brass quick disconnect coupling DN 7.2

Artikel

Opis	Ø cevi znotraj (mm)	Ø cevi zunaj (mm)	maks. delovni tlak pri 20°C (bar)	dolžina cevi (m)
K- 07 10 11 91	6,3	11,0	15	5
K- 07 10 11 85	6,3	11,0	15	10
K- 07 10 11 87	6,3	11,0	15	15
K- 07 10 11 88	6,3	11,0	15	20
K- 07 10 11 90	6,3	11,0	15	25
K- 07 10 11 99	9,0	14,5	15	5
K- 07 10 11 93	9,0	14,5	15	10
K- 07 10 11 95	9,0	14,5	15	15
K- 07 10 11 96	9,0	14,5	15	20
K- 07 10 11 98	9,0	14,5	15	25