

K-L-STECKVER AG-K

Male elbows, conical male thread

HANSA FLEX

Lastnosti

| | |
|---------------------|---------------------|
| delovni tlak | Max. 16 bar |
| delovna temperatura | -20 °C to +80 °C |
| Material: | ponikljana medenina |
| potisni obroč | Hostaform |
| vpenjalni obroč | Stainless steel |



Navodilo

Drugi podatki na zahtevo.

Opis

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Artikel

| Opis | Navoj | za zunanji Ø mm cevi | L1 (mm) | L2 (mm) | zev ključa |
|----------------|-------|----------------------|------------|------------|------------|
| K- 07 40 25 65 | R 1/8 | 4 mm | 18,6 | 16,0 | 10 mm |
| K- 07 40 25 66 | R 1/8 | 6 mm | 21,9 | 16,0 | 10 mm |
| K- 07 40 25 67 | R 1/8 | 8 mm | 25,4 | 16,0 | 10 mm |
| K- 07 40 25 63 | R 1/4 | 6 mm | 21,9 | 18,5 | 10 mm |
| K- 07 40 25 64 | R 1/4 | 8 mm | 25,4 | 18,5 | 10 mm |
| K- 07 40 25 62 | R 1/4 | 10 mm | 27,2 | 22,0 | 14 mm |