

# K-SCHOTT-STECKVERB IG-K

Male bulkhead connectors, conical female thread

**HANSA FLEX**

## Lastnosti

|                     |  |
|---------------------|--|
| delovni tlak        | Max. 15 bar, coarse vacuum   |
| Območje uporabe     | Air, vacuum  |
| priporočene cevi    | PU or PA (nylon)   |
| Sredstva            | Compressed air and all gases or liquids that are compatible with the materials |
| območje temperatur: | -20 °C to +80 °C   |
| tesnilna ploskev    | Conical version: thread coating  |
| Material:           | Plastic, Nickel plated brass   |
| potisni obroč       | Plastic  |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikel

| Opis           | Navoj  | za zunanji Ø mm cevi | navoj stikalne plošče | L1 (mm) | zev ključa |
|----------------|--------|----------------------|-----------------------|---------|------------|
| K- 07 40 04 42 | Rc 1/8 | 4 mm                 | M 12 x 1              | 23,8    | 14 mm      |
| K- 07 40 04 43 | Rc 1/8 | 6 mm                 | M 14 x 1              | 27,0    | 17 mm      |
| K- 07 40 04 44 | Rc 1/8 | 8 mm                 | M 16 x 1              | 32,1    | 19 mm      |
| K- 07 40 04 40 | Rc 1/4 | 6 mm                 | M 14 x 1              | 30,0    | 17 mm      |
| K- 07 40 04 41 | Rc 1/4 | 8 mm                 | M 16 x 1              | 35,1    | 19 mm      |
| K- 07 40 04 38 | Rc 1/4 | 10 mm                | M 20 x 1              | 36,0    | 24 mm      |
| K- 07 40 04 39 | Rc 1/4 | 12 mm                | M 22 x 1              | 38,1    | 24 mm      |
| K- 07 40 04 45 | Rc 3/8 | 10 mm                | M 20 x 1              | 37,0    | 24 mm      |
| K- 07 40 04 46 | Rc 3/8 | 12 mm                | M 22 x 1              | 39,1    | 24 mm      |
| K- 07 40 04 37 | Rc 1/2 | 12 mm                | M 22 x 1              | 41,1    | 24 mm      |