


# K-T-STECK VERS ISK DREH AG-K

Male branch tees with inner hex, swivel type, conical male thread, coated

**HANSA FLEX**

## Lastnosti

delovni tlak	Max. 15 bar, coarse vacuum
Območje uporabe	Air, vacuum
priporočene cevi	PU or PA (nylon)
Sredstva	Compressed air and all gases or liquids that are compatible with the materials
območje temperatur:	-20 °C to +80 °C
tesnilna ploskev	Conical version: thread coating
Material:	Plastic, Nickel plated brass
potisni obroč	Plastic



## Navodilo

Drugi podatki na zahtevo.

## Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikel

Opis	Navoj	za zunanji Ø mm cevi	inbus (mm)	L1 (mm)	L2 (mm)	zav ključa
K- 07 40 05 41	R 1/8	4 mm	4,0	45,0	29,0	14 mm
K- 07 40 05 42	R 1/8	6 mm	4,0	42,6	29,0	14 mm
K- 07 40 05 43	R 1/8	8 mm	4,0	48,5	29,0	14 mm
K- 07 40 05 39	R 1/4	6 mm	6,0	46,7	38,0	17 mm
K- 07 40 05 40	R 1/4	8 mm	6,0	52,5	38,0	17 mm
K- 07 40 05 37	R 1/4	10 mm	6,0	59,6	38,0	17 mm
K- 07 40 05 38	R 1/4	12 mm	6,0	61,2	38,0	17 mm
K- 07 40 05 46	R 3/8	8 mm	8,0	56,3	39,7	20 mm
K- 07 40 05 44	R 3/8	10 mm	8,0	63,5	39,7	20 mm
K- 07 40 05 45	R 3/8	12 mm	8,0	64,9	39,7	20 mm