

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Lastnosti

Notranja plast Soft-PVC, black

Vloga poliestrska pletenina

Zunanja plast Soft-PVC, blue

temperatura -20 °C to +60 °C

dolžina valjev 50 m



Navodilo

Drugi podatki na zahtevo.

Opis

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.).

Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Artikel

Opis	Ø cevi znotraj (mm)	Ø cevi zunaj (mm)	Max. working pressure resistance at 23°C (bar)	Polmer upogiba min. (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88