

# K-STECKVERBINDU RED 1

Reducers

**HANSA FLEX**

## Lastnosti

|                     |                     |
|---------------------|---------------------|
| delovni tlak        | Max. 16 bar         |
| delovna temperatura | -20 °C to +80 °C    |
| Material:           | ponikljana medenina |
| potisni obroč       | Hostaform           |
| vpenjalni obroč     | Stainless steel     |



## Navodilo

Drugi podatki na zahtevo.

## Opis

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Artikel

| Opis           | Navoj    | za zunanji Ø mm cevi | L1<br>(mm) |
|----------------|----------|----------------------|------------|
| K- 07 40 25 26 | M 13 x 1 | 4 mm / 6 mm          | 32,7       |
| K- 07 40 25 27 | M 15 x 1 | 4 mm / 8 mm          | 34,4       |
| K- 07 40 25 28 | M 15 x 1 | 6 mm / 8 mm          | 35,0       |
| K- 07 40 25 29 | M 17 x 1 | 6 mm / 10 mm         | 37,5       |
| K- 07 40 25 30 | M 20 x 1 | 6 mm / 12 mm         | 39,0       |
| K- 07 40 25 31 | M 17 x 1 | 8 mm / 10 mm         | 37,8       |
| K- 07 40 25 32 | M 20 x 1 | 8 mm / 12 mm         | 40,1       |
| K- 07 40 25 33 | M 20 x 1 | 10 mm / 12 mm        | 40,8       |