

# K-LKM S NW7,2 SCHL TUE

Safety couplings DN 7.2, with hose stem

**HANSA FLEX**

## Lastnosti

<b>Obratovalni tlak</b>	0 - 35 bar, maximum static working pressure (non-pulsating)
<b>pretok zraka</b>	1.100 l/min (at $\Delta p = 0.5$ bar)
<b>temperatura medija</b>	-30 °C to +100 °C
<b>ohišje, puša, ohišje ventila</b>	Nickel-plated brass
<b>vzmet, kroglice</b>	Stainless-steel
<b>tesnilni material</b>	NBR



## Navodilo

Drugi podatki na zahtevo.

## Opis

One-hand safety coupling with double locking mechanism. Connection: Similar to standard couplings, simply by pressing the plug into the coupling.

Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

## Artikel

Opis	Priključek	dolžina (mm)	SW (mm)
K- 07 35 02 87	Stem, I.D. 6	60,0	22
K- 07 35 02 88	Stem, I.D. 8	60,0	22
K- 07 35 02 89	Stem, I.D. 9	60,0	22
K- 07 35 02 90	Stem, I.D. 10	60,0	22
K- 07 35 02 91	Stem, I.D. 13	60,0	22

## Dodatni elementi

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,