

# K-DLV MULTI-LINK OHNE KUPPLU

Compressed air distributor, type »Multi-Link« without couplings, female thread

**HANSA FLEX**

## Lastnosti

<b>Obratovalni tlak</b>	Max. 16 bar
<b>območje temperatur:</b>	-20 °C do +100 °C (-20 °C to +80 °C quickconnect-safety couplings)
<b>Material:</b>	Galvanised steel / brass
<b>Priključek</b>	G 1/2 female
<b>Sredstva</b>	Compressed air, non-corrosive gases
<b>tesnilni material</b>	NBR



## Navodilo

Drugi podatki na zahtevo.

## Opis

Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 1 to 5 bleed units, optionally with:

- G 1/2 female threaded connection for individually adaption output segments,
- DN 7.6 standard quick disconnect couplings,
- DN 7.6 quick disconnectsafety couplings.

## Artikel

Opis	Priključek	enote za odvzem
K- 07 35 13 68	G 1/2 female	1
K- 07 35 13 71	G 1/2 female	2
K- 07 35 13 74	G 1/2 female	3
K- 07 35 13 77	G 1/2 female	4
K- 07 35 13 80	G 1/2 female	5