

# K-DLV MULTI-LINK STANDARD

Compressed air distributor, type »Multi-Link« with quick disconnect standard couplings DN 7.6

**HANSA FLEX**

## Lastnosti

|                     |                                     |
|---------------------|-------------------------------------|
| Obratovalni tlak    | Max. 16 bar                         |
| območje temperatur: | -20 °C do +100 °C                   |
| Material:           | Galvanised steel / brass            |
| Priključek          | G 1/2 female                        |
| Sredstva            | Compressed air, non-corrosive gases |
| tesnilni material   | NBR                                 |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 1 to 5 bleed units:  
- DN 7.6 standard quick disconnect couplings.

## Artikel

| Opis           | Priključek                | enote za odvzem |
|----------------|---------------------------|-----------------|
| K- 07 35 13 69 | Standard couplings DN 7.6 | 1               |
| K- 07 35 13 72 | Standard couplings DN 7.6 | 2               |
| K- 07 35 13 75 | Standard couplings DN 7.6 | 3               |
| K- 07 35 13 78 | Standard couplings DN 7.6 | 4               |
| K- 07 35 13 81 | Standard couplings DN 7.6 | 5               |