

K-LECKAGESUCHGERÄT

Leakage finder

HANSA FLEX

Lastnosti

delovna frekvenca	40 kHz \pm 2 kHz
Priključek	4-pin connection for headphones and charger, 3.5 mm stereo jack for connecting sensor and cable
laser	Wave length: 655 to 660 nm, Output power: 0.4 to 0.5 mW
napajanje z energijo	Internal NiMH rechargeable battery
trajanje delovanja	Approx. 6 hours without laser / 4 hours with laser
čas polnjenja	Approx. 1.5 hours
temperatura uporabe	0 °C to +40 °C
temperatura ležaja	-10 °C to +50 °C



Navodilo

Drugi podatki na zahtevo.

Opis

Function: The annual energy cost of leaks in pneumatic and gas systems are high and avoidable. When these gases flow unused out of leaks, they create noises inaudible to the human ear. With the LS 100, even the smallest leaks can be heard from several metres distance. It transforms inaudible signals to a frequency that can be detected visually on the display and acoustically with the supplied sound-proof headphones. Use: leakage inspections of pneumatic, gas, steam and vacuum systems.
The advantages of the LS 100: Simple and quick measurement, even from distances of several metres. Measurements can be taken on running systems, without affecting their operation. The device is quickly amortised by the high cost savings.

Artikel

Opis	opis
K- 07 25 19 53	Leak detection device, including accessories in a practical carrying case

Pribor

K-ALU-TELESKOPSTANGE	Aluminium-telescopic pole
----------------------	---------------------------