

# K-ROHRDOPPELNIPPEL VA

Double pipe nipples, stainless steel 1.4571

**HANSA FLEX**

## Lastnosti

|                  |                       |
|------------------|-----------------------|
| delovni tlak     | Max. 20 bar           |
| priključni navoj | R-thread to EN 10226  |
| Material:        | legirano jeklo 1.4571 |



## Navodilo

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Drugi podatki na zahtevo.

## Artikel

| Opis           | Navoj   | dolžina (mm) |
|----------------|---------|--------------|
| K- 07 40 48 61 | R 1/4   | 40,0         |
| K- 07 40 48 62 | R 1/4   | 60,0         |
| K- 07 40 48 63 | R 1/4   | 80,0         |
| K- 07 40 48 56 | R 1/4   | 100,0        |
| K- 07 40 48 57 | R 1/4   | 120,0        |
| K- 07 40 48 58 | R 1/4   | 150,0        |
| K- 07 40 48 59 | R 1/4   | 180,0        |
| K- 07 40 48 60 | R 1/4   | 200,0        |
| K- 07 40 48 85 | R 3/8   | 40,0         |
| K- 07 40 48 86 | R 3/8   | 60,0         |
| K- 07 40 48 87 | R 3/8   | 80,0         |
| K- 07 40 48 80 | R 3/8   | 100,0        |
| K- 07 40 48 81 | R 3/8   | 120,0        |
| K- 07 40 48 82 | R 3/8   | 150,0        |
| K- 07 40 48 83 | R 3/8   | 180,0        |
| K- 07 40 48 84 | R 3/8   | 200,0        |
| K- 07 40 48 53 | R 1/2   | 40,0         |
| K- 07 40 48 54 | R 1/2   | 60,0         |
| K- 07 40 48 55 | R 1/2   | 80,0         |
| K- 07 40 48 48 | R 1/2   | 100,0        |
| K- 07 40 48 49 | R 1/2   | 120,0        |
| K- 07 40 48 50 | R 1/2   | 150,0        |
| K- 07 40 48 51 | R 1/2   | 180,0        |
| K- 07 40 48 52 | R 1/2   | 200,0        |
| K- 07 40 48 77 | R 3/4   | 40,0         |
| K- 07 40 48 78 | R 3/4   | 60,0         |
| K- 07 40 48 79 | R 3/4   | 80,0         |
| K- 07 40 48 72 | R 3/4   | 100,0        |
| K- 07 40 48 73 | R 3/4   | 120,0        |
| K- 07 40 48 74 | R 3/4   | 150,0        |
| K- 07 40 48 75 | R 3/4   | 180,0        |
| K- 07 40 48 76 | R 3/4   | 200,0        |
| K- 07 40 48 29 | R 1     | 40,0         |
| K- 07 40 48 30 | R 1     | 60,0         |
| K- 07 40 48 31 | R 1     | 80,0         |
| K- 07 40 40 93 | R 1     | 150,0        |
| K- 07 40 48 25 | R 1     | 100,0        |
| K- 07 40 48 26 | R 1     | 120,0        |
| K- 07 40 48 27 | R 1     | 180,0        |
| K- 07 40 48 28 | R 1     | 200,0        |
| K- 07 40 48 45 | R 1 1/4 | 40,0         |
| K- 07 40 48 46 | R 1 1/4 | 60,0         |
| K- 07 40 48 47 | R 1 1/4 | 80,0         |
| K- 07 40 48 40 | R 1 1/4 | 100,0        |
| K- 07 40 48 41 | R 1 1/4 | 120,0        |



# K-ROHRDOPPELNIPPEL VA

Double pipe nipples, stainless steel 1.4571

## Artikel

| Opis           | Navoj   | dolžina<br>(mm) |
|----------------|---------|-----------------|
| K- 07 40 48 42 | R 1 1/4 | 150,0           |
| K- 07 40 48 43 | R 1 1/4 | 180,0           |
| K- 07 40 48 44 | R 1 1/4 | 200,0           |
| K- 07 40 48 37 | R 1 1/2 | 40,0            |
| K- 07 40 48 38 | R 1 1/2 | 60,0            |
| K- 07 40 48 39 | R 1 1/2 | 80,0            |
| K- 07 40 48 32 | R 1 1/2 | 100,0           |
| K- 07 40 48 33 | R 1 1/2 | 120,0           |
| K- 07 40 48 34 | R 1 1/2 | 150,0           |
| K- 07 40 48 35 | R 1 1/2 | 180,0           |
| K- 07 40 48 36 | R 1 1/2 | 200,0           |
| K- 07 40 48 69 | R 2     | 40,0            |
| K- 07 40 48 70 | R 2     | 60,0            |
| K- 07 40 48 71 | R 2     | 80,0            |
| K- 07 40 48 64 | R 2     | 100,0           |
| K- 07 40 48 65 | R 2     | 120,0           |
| K- 07 40 48 66 | R 2     | 150,0           |
| K- 07 40 48 67 | R 2     | 180,0           |
| K- 07 40 48 68 | R 2     | 200,0           |