

# K-XG LOESBAR IG IG FLACHDICHT

Detachable double nipples, female, flat seat

**HANSA FLEX**

## Lastnosti

|                |                              |
|----------------|------------------------------|
| delovni tlak   | Max. 10 bar                  |
| zunani navoj   | Parallel to DIN EN ISO 228-1 |
| notranji navoj | Parallel to DIN EN ISO 228-1 |
| Material:      | Stainless steel 1.4408       |



## Navodilo

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Drugi podatki na zahtevo.

## Artikel

| Opis           | Navoj   | L1<br>(mm) | zev ključa 1<br>(mm) | zev ključa 2<br>(mm) |
|----------------|---------|------------|----------------------|----------------------|
| K- 07 40 45 85 | G 1/8   | 32,3       | 29                   | 18                   |
| K- 07 40 45 94 | G 1/4   | 32,4       | 29                   | 18                   |
| K- 07 40 45 95 | G 3/8   | 34,7       | 34                   | 22                   |
| K- 07 40 46 00 | G 1/2   | 40,0       | 39                   | 26                   |
| K- 07 40 46 01 | G 3/4   | 42,0       | 47                   | 32                   |
| K- 07 40 46 02 | G 1     | 48,7       | 58                   | 40                   |
| K- 07 40 46 03 | G 1 1/4 | 54,0       | 67                   | 49                   |
| K- 07 40 46 04 | G 1 1/2 | 58,9       | 76                   | 56                   |
| K- 07 40 46 05 | G 2     | 62,2       | 90                   | 68                   |