

# K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass

**HANSA FLEX**

## Lastnosti

vrsta priključka connection nipples and coupling NW 7,2

delovna temperatura -40 °C to +74 °C



## Navodilo

Drugi podatki na zahtevo.

## Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Artikel

| Opis           | Ø cevi znotraj (mm) | Ø cevi zunaj (mm) | Ø zunanje navitje (mm) | Max. working pressure resistance at 23°C (bar) | maks. delovna dolžina (m) |
|----------------|---------------------|-------------------|------------------------|--|---------------------------|
| K- 07 10 12 72 | 5,0                 | 8,0               | 40                     | 10   | 3,0                       |
| K- 07 10 12 74 | 5,0                 | 8,0               | 40                     | 10   | 6,0                       |
| K- 07 10 12 76 | 5,0                 | 8,0               | 40                     | 10   | 7,5                       |
| K- 07 10 12 81 | 6,3                 | 9,5               | 60                     | 10   | 3,0                       |
| K- 07 10 12 83 | 6,3                 | 9,5               | 60                     | 10   | 6,0                       |
| K- 07 10 12 85 | 6,3                 | 9,5               | 60                     | 10   | 7,5                       |
| K- 07 10 12 79 | 6,3                 | 9,5               | 60                     | 10   | 10,0                      |
| K- 07 10 12 90 | 8,0                 | 12,0              | 80                     | 9  | 3,0                       |
| K- 07 10 12 92 | 8,0                 | 12,0              | 80                     | 9  | 6,0                       |
| K- 07 10 12 94 | 8,0                 | 12,0              | 80                     | 9  | 7,5                       |
| K- 07 10 12 88 | 8,0                 | 12,0              | 80                     | 9  | 10,0                      |

## Pribor

K-DREHBARE VERSCHRAUBUNG Swivel adapters