# K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

HANSA-FLEX

## Lastnosti

| | |
|---|---|
| **vrsta priključka** | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| **delovna temperatura** | -40 °C to +74 °C |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.
Ni primerno za udarna ali impulzna orodja!

## Artikel

| Opis | Ø cevi znotraj (mm) | Ø cevi zunaj (mm) | Ø zunanje navitje (mm) | Max. working pressure resistance at 23°C (bar) | maks. delovna dolžina (m) |
|---|---|---|---|---|---|
| **K- 07 10 12 71** | 5,0 | 8,0 | 40 | 10 | 3,0 |
| **K- 07 10 12 73** | 5,0 | 8,0 | 40 | 10 | 6,0 |
| **K- 07 10 12 75** | 5,0 | 8,0 | 40 | 10 | 7,5 |
| **K- 07 10 12 80** | 6,3 | 9,5 | 60 | 10 | 3,0 |
| **K- 07 10 12 82** | 6,3 | 9,5 | 60 | 10 | 6,0 |
| **K- 07 10 12 84** | 6,3 | 9,5 | 60 | 10 | 7,5 |
| **K- 07 10 12 78** | 6,3 | 9,5 | 60 | 10 | 10,0 |
| **K- 07 10 12 89** | 8,0 | 12,0 | 80 | 9 | 3,0 |
| **K- 07 10 12 91** | 8,0 | 12,0 | 80 | 9 | 6,0 |
| **K- 07 10 12 93** | 8,0 | 12,0 | 80 | 9 | 7,5 |
| **K- 07 10 12 87** | 8,0 | 12,0 | 80 | 9 | 10,0 |

## Pribor

| | |
|---|---|
| **K-DREHBARE VERSCHRAUBUNG** | Swivel adapters |

*Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.*