K-DIGI DRUCKSCHA H DURCHF IA PF2A

Digital Flow Switch PF2Ax795

Lastnosti

Način izdelave	Digital Flow Switch
maks. delovni tlak	0,1 MPa
min. delovni tlak	1.50 MPa
nazivna napetost	24 V DC
potrebni tok	150 mA
prikaz delovanja	3 digits, 7-Segment-LED lights at output signal = ON: OUT1: green, OUT2: red)
I/O kabel	without connection cable
razred zaščite	IP 65
temperatura medija	0 °C to +50 °C
temperatura okolice	0 °C to +50 °C
Sredstva	Air and nitrogen
serija	PF2A
drugi podatki	for High flow Integrated Display Type



Opis

Digital flow switch for high flow, series PF2A, for dry air, with integrated display unit, measuring range 30 to 3000 l/min, smallest adjustment unit 5 l/min, media temperature 0 to 50 °C, operating temperature range 0 to 50 °C, repetition accuracy max. ±3% of the measuring range, temperature characteristic max. ±2% of the measuring range. (0 to 50 °C, based on 25 °C), current consumption max. 150 mA, measuring principle thermistor (heating element), operating display 3-digit, 7-segment LED (illuminates at output signal ON OUT1: Green
OUT2: Red), operating pressure range 0.1 to 1.5 MPa, switch output PNP open collector 1 output and 1 analogue output (4 to 20 mA), with function to switch over the display unit, supply voltage 24 VDC, protection class IP 65, connection cable not included,connection size G 1 1/2

Artikel

Opis	Priključni navoj	enota nastavitve [min.] (L/min)	Mersko območje	ponovljivost
K- 07 50 00 30	G 1	5,00	30 bis 3000 l/min	max. ±3 % from scale
K- 07 50 00 33	G 1 1/2	10,00	60 bis 6000 l/min	max. ±3 % from scale
K- 07 50 00 38	G 2	10,00	120 bis 12000 l/min	max. ±3 % from scale

Kljub skrbnemu preverjanju napak ne moremo izključiti in za informacije, ki so tu navedene, ne prevzemamo nobene odgovornosti.