

K-ROHRLEIT ALU KALIBRIERT GRAU INFI

Pipe made of aluminium, calibrated, grey

HANSA FLEX

Lastnosti

| | |
|-------------------------|--|
| Sredstva | Compressed air, vacuum, inert gases |
| razteznostni koeficient | 0,024 mm/m °C |
| Obratovalni tlak | -0,99 bar - 15 bar |
| območje temperatur: | -20 °C to +80 °C |
| Barva | greyRAL 7035 |
| Material: | Aluminium UNI 9006/1 Al Mg 0,5 Si 0,4 Fe 0,2 |
| obdelava površine | electrostatic coating |



Navodila za naročanje

Special lengths on request

Artikel

| Opis | Zunanji Ø (mm) | debelina stene (mm) | Teža na m (kg) | specifična teža na dm ³ (kg) | dolžina (m) | Embalažna enota |
|----------------|-------------------|------------------------|-------------------|--|----------------|-----------------|
| K- 07 40 53 15 | 20 | 1,5 | 0,235 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 30 | 20 | 1,5 | 0,235 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 16 | 25 | 1,5 | 0,298 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 31 | 25 | 1,5 | 0,298 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 17 | 32 | 1,5 | 0,387 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 32 | 32 | 1,5 | 0,387 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 18 | 40 | 1,5 | 0,490 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 33 | 40 | 1,5 | 0,490 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 19 | 50 | 2,0 | 0,814 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 34 | 50 | 2,0 | 0,814 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 20 | 63 | 2,0 | 1,034 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 35 | 63 | 2,0 | 1,034 | 2,7 | 6,000 | 1 piece |
| K- 07 40 55 08 | 80 | 2,0 | 1,493 | 2,7 | 4,000 | 1 piece |
| K- 07 40 55 10 | 80 | 2,0 | 1,493 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 21 | 110 | 2,5 | 2,280 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 36 | 110 | 2,5 | 2,280 | 2,7 | 6,000 | 1 piece |