

K-DIGI DRUCKSCHA H 3 DURCHF PF2A

Digital Flow Switch high flow version PF2A

HANSA**FLEX**

Lastnosti

| | |
|---------------------|--|
| Način izdelave | Digital Flow Switch |
| maks. delovni tlak | -50 kPa |
| nazivna napetost | 24 V DC |
| prikaz delovanja | 3 digits, 7-Segment-LED lights at output signal = ON: OUT1: green, OUT2: red) |
| I/O kabel | without connection cable |
| razred zaščite | IP 65 |
| temperatura medija | 0 °C to +50 °C |
| temperatura okolice | 0 °C to +50 °C |
| Sredstva | Air and nitrogen |
| serija | PF2A |
| drugi podatki | for air and nitrogen Three types of output: Switch, accumulated pulse and analog outputs \nSwitching of current flow to accumulated flow is possible |



Opis

Digital flow switch, series PF2A, for air and nitrogen, three output types: Switch, accumulated pulse and analogue outputs, switching from real-time flow rate to accumulated flow is possible, measuring range 1 to 10 l/min, media temperature 0 to 50 °C, operating temperature range 0 to 50 °C, repetition accuracy max. ±3% of the measuring range, temperature characteristic max. 5% of the measuring range. (0 to 50 °C, based on 25 °C), current consumption (no load) max. 170 mA, measuring principle thermistor (heating element), operating display 3-digit, 7-segment LED (illuminates at output signal ON OUT1: Green

OUT2: Red), operating pressure range -50 kPa... 0.5 MPa, switch output PNP open collector internal voltage drop max. 1.5 V (at 80 mA working current)

2 outputs, supply voltage 12 to 24 VDC, protection class IP 65, connection size G 1/4

Artikel

| Opis | Priključni navoj | Mersko območje | min. delovni tlak (MPa) | potrebni tok max. (mA) | ponovljivost |
|---------------|------------------|------------------|-------------------------|------------------------|----------------------|
| K-07 50 00 34 | G 1/4 | 1 bis 10 l/min | 0,50 | 170 | max. ±3 % from scale |
| K-07 50 00 35 | G 3/8 | 10 bis 100 l/min | 0,50 | 170 | max. ±3 % from scale |
| K-07 50 00 39 | G 3/8 | 20 bis 200 l/min | 0,50 | 170 | max. ±3 % from scale |
| K-07 50 00 40 | G 1/4 | 5 bis 50 l/min | 0,50 | 170 | max. ±1 % from scale |
| K-07 50 00 41 | G 1/2 | 50 bis 500 l/min | 0,50 | 170 | max. ±3 % from scale |