

# K-DBV MANO 1/2"

Pressure limiting valves size 1/2"

## Lastnosti

|                            |  |
|----------------------------|--|
| <b>Način izdelave</b>      | Spring-loaded, non-return diaphragm valve with adjustable opening pressure |
| <b>temperatura medija</b>  | max. 60 °C   |
| <b>temperatura okolice</b> | Max. 60 °C   |
| <b>tesnilni material</b>   | NBR  |
| <b>vzmetni pokrov</b>      | POM/brass  |
| <b>ohišje</b>              | Die-cast zinc, painted silver  |
| <b>membrana</b>            | NBR  |



## Navodilo

Drugi podatki na zahtevo.

## Opis

Manually adjustable overflow valves. For protecting pneumatic systems against damage caused by excess pressure.

## Artikel

| Opis           | Navoj | regulacijsko območje | A<br>(mm) | B        | C<br>(mm) | D<br>(mm) |
|----------------|-------|----------------------|-----------|----------|-----------|-----------|
| K- 07 25 01 97 | G 1/2 | 0.5 - 3.0 bar        | 82,0      | 162,0 mm | 129,0     | 33,0      |
| K- 07 25 01 98 | G 1/2 | 0.5 - 5.5 bar        | 82,0      | 162,0 mm | 129,0     | 33,0      |
| K- 07 25 01 99 | G 1/2 | 0.5 - 10.0 bar       | 82,0      | 162,0 mm | 129,0     | 33,0      |

## Nadomestni deli

|                                    |  |
|------------------------------------|--|
| <b>K-HALTERBAUSATZ STANDARD</b>    | Holder   |
| <b>K-GERAETESTECKER</b>            | Coupling socket  |
| <b>K-SCHALLDAE SINTERBR AG 569</b> | Silencers, sintered bronze, flat type with male thread, 569 Series |
| <b>K-VERSCHLEI-SATZ</b>            | Set of wearing parts   |
| <b>K-KM MS</b>                     | Hexagonal lock nuts, brass   |